



# SP140

## High-Performance WOR Fabric Protectant

Revised March 29, 2009

### Characteristics

- |   |   |
|---|---|
| • Imparts excellent water and oil repellency (WOR) to <b>polyester, cotton, and wool.</b> | Resistant to rain as well as water- and oil-based stains                                      |
| • Water-based emulsion  | Non-flammable – no flash point  |
| • High solid and fluorine content   | High bath concentrations are not necessary  |
| • Application methods   | Spray, foam, knife-coat, kiss roll, exhaust, and traditional padding or “Dip & Nip” processes |
| • Compatibility   | Fluoropolymer-compatible wetting agents, extenders, wrinkle free resins, and fabric softeners |
| • APEO-free   | Does not contain APEOs (alkyl phenol ethylene oxides)   |

### Properties

- |                     |  |
|---------------------|--|
| • Composition       | Fluoropolymer emulsion   |
| • Ionic Charge      | Weakly cationic  |
| • Appearance        | Off-white or pale yellow emulsion  |
| • pH                | Acidic   |
| • Specific Gravity  | 1.1 g/mL @ 25 °C   |
| • Solubility        | Readily soluble in cold water  |
| • Storage stability | Stable for 1 year at 20 °C – avoid freezing and temperatures above 40 °C |

### Applications

SP140 can be applied in spray, foam, knife-coat, kiss roll, exhaust, or traditional padding applications. For application suggestions, please see the Application Information Sheet.